

# MAG2430 Help Intercom Extended Controller



## *Features*

- With high-end aluminum alloy brushed panel, the appearance of the panel is novel.
- With built-in high-fidelity, directional condenser microphones;
- Built-in monitor speaker for clear voice.
- With one-touch for help functions and status indicators to show the work status clearly.
- Achieving two-way talk;
- Powered by 100 Gigabit PoE switch

## *Description*

The MAG2430 Intercom for Help Extension based on local area network digital audio transmission technology, is of high performance and high fidelity. It calls for help with one-touch, widely used in many situations.

## *Specification*

Indicator Items		Parameters:
Model		MAG2430
Monitoring Speaker	Rated Output	$\geq 0.25\text{W}$
	Frequency	200~11KHz( $\pm 3\text{dB}$ )
	Distortion	$\leq 1\%$
	SNR	$\geq 65\text{dB}$
	Input	4 $\Omega$
Pickup microphone		Capacitive
Sensitivity		$\geq 50\text{mV}$
Static Current		$\leq 100\text{mA}$
Work Current		$\leq 200\text{mA}$
Data Interface		Network Interface
Function Button		Call for help
Power Supply		PoE +48V
Packing Size (L×W×H mm)		280×250×110
Machine Dimension (L×W×H mm)		178×94×54
Gross weight		1kg
Net Weight		0.7kg

